



FLECK 5812

CV

HIGH PERF FLEXIBLE



FEATURES/BENEFITS

Fiber-reinforced polypropylene for superior strength, non-crosive, and continuous strength

a e w s d n a P a a P



VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4", 1", or 1-1/4" NPT/ BSP/Sweat
Cycles	5

FLOW RATES (50 PSI INLET) – VALVE ALONE - 2.5" BASE

Piston	Downflow	Upflow	Filter
Continuous (15 psi drop)	43 GPM 9.9 m ³ /hr	39 GPM 8.9 m ³ /hr	37 GPM 8.4 m ³ /hr
Peak (25 psi drop)	56 GPM 12.7 m ³ /hr	51 GPM 11.9 m ³ /hr	47 GPM 10.7 m ³ /hr
Cv (flow at 1 psi drop)	11.2	10.1	9.4
Max. Backwash (25 psi drop)	33 GPM 7.5 m ³ /hr	36 GPM 8.1 m ³ /hr	45 GPM 9.9 m ³ /hr

FLOW RATES (50 PSI INLET) – VALVE ALONE - 4" BASE

Piston	Downflow	Upflow	Filter
Continuous (15 psi drop)	45 GPM 10.3 m ³ /hr	40 GPM 9.1 m ³ /hr	38 GPM 8.7 m ³ /hr
Peak (25 psi drop)	59 GPM 13.3 m ³ /hr	52 GPM 11.7 m ³ /hr	50 GPM 11.3 m ³ /hr
Cv (flow at 1 psi drop)	11.7	10.3	9.9
Max. Backwash (25 psi drop)	34 GPM 7.8 m ³ /hr	36 GPM 8.2 m ³ /hr	45 GPM 10.2 m ³ /hr

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available	
SXT:	0 - 199 min/cycle
XTR2:	0 - 240 min/cycle

METER INFORMATION

Meter Accuracy	
1-1/4" Turbine:	2 - 40 GPM ± 5% (0.45 - 9 m ³ /h)
Meter Capacity Range	
SXT:	1 - 999,900 gal (0 - 3,785 m ³)
XTR2:	1 - 9,999,999 gal (0 - 378,541 m ³)

DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm) 32 mm I.D. 1" I.D. (25.4 mm)
Drain Line	1.5" NPTF Quick-Connect
Brine Valve	
1600:	3/8"
Injector System	1610
Mounting Base	2.5" - 8 NPSM 4" - NPSM
Height from Top of Tank	12" (305 mm)
Riser Height	1/4" Below top of tank

TYPICAL APPLICATIONS

Water Softener	8 - 24" diameter
Filters	8 - 24" diameter based on 10 GPM/ft ²

ADDITIONAL INFORMATION

Electrical Rating	12 Volts DC
Estimated Shipping Weight	12 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)



PENTAIR WATER QUALITY SYSTEMS

5730 ... A ... A ... A ... 53209

... : 262.238.4400 ... : 262.238.4404

... A ... CA ... A ... C

... CA ... : 800.279.9404

2015 ... C. A ...

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4004319 REV A MR15